

Material Safety Data Sheet

CS: 1.4.93

Page: 1 of 5

Infosafe No™ 5FUXG Issue Date : August 2007 ISSUED by FUCHS

Product Name : ISUZU CAB TILT (ISO68)

Not classified as hazardous

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name ISUZU CAB TILT (ISO68)
Product Code 3912
Company Name ISUZU Australia Limited (ABN 97 006 962 572)
Address 858 Lorimer Street Port Melbourne
VIC 3207 Australia
Emergency Tel. 1800 638 556 (24hr AUST), 0800 154 166 (24hr NZ).
Telephone/Fax Number Tel: 03-96446666
Fax: 03-96446622
Recommended Use Supplied as a zinc free hydraulic oil for use in suitable applications only.

2. HAZARDS IDENTIFICATION

Hazard Classification Not classified as hazardous
NON-HAZARDOUS SUBSTANCE.
NON-DANGEROUS GOODS.
Hazard classification according to the criteria of NOHSC.
Dangerous goods classification according to the Australia Dangerous Goods Code.

Risk Phrase(s) Not classified as hazardous

Irritancy of Product Not classified as an irritant.

Sensitization of Product Not known to be a sensitiser.

Teratogenicity No teratogenic effects known.

Other Information Used oils and greases may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and environment on disposal. All used oils and greases should be handled with caution and skin contact avoided as far as possible.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization Liquid

Ingredients	Name	CAS	Proportion	Hazard Symbol	Risk Phrase
	Mineral Oil	Not required	70-100 %		
	Ingredients determined not to be hazardous	Mixture	0-30 %		
	Hydroxyalkyl carboxylic ester	Confidential	0-0.09 %	Xi	R38

Other Information The petroleum oils in this product contain less than 3% DMSO extract as measured by the IP 346 test method.

4. FIRST AID MEASURES

Inhalation Remove victim from exposure - avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have qualified person give oxygen through a face mask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage.

Ingestion Give water to drink. DO NOT induce vomiting. Seek medical attention. If vomiting occurs get immediate medical attention due to aspiration risk.

Skin Wash with plenty of soap and water. If irritation occurs seek medical advice. Remove contaminated clothing and wash before re-use. If material is injected under skin, seek medical attention to prevent serious damage. Do not wait for symptoms to develop. Show this MSDS to the doctor drawing attention to 'Advice to doctor' section.

Material Safety Data Sheet

CS: 1.4.93

Page: 2 of 5

Infosafe No™ 5FUXG	Issue Date : August 2007	ISSUED by FUCHS
--------------------	--------------------------	-----------------

Product Name : **ISUZU CAB TILT (ISO68)**

Not classified as hazardous

Eye	Immediately irrigate with copious quantity of water for at least 15 minutes. Eyelids to be held open. In all cases of eye contamination it is a sensible precaution to seek medical advice.
First Aid Facilities	Normal washroom facilities are generally suitable. Ensure an eyewash station and safety shower are available and ready for use.
Advice to Doctor	Treat symptomatically. Subcutaneous injection from high-pressure equipment can leave a small, sometimes bloodless, puncture wounds deep into the extremity. Within 24 hours, there is usually extensive swelling, discolouration and intense pain in the affected part. Requires immediate treatment at a surgical emergency centre, otherwise disfigurement of affected part may occur. Treatment of high pressure wounds may include: 1. Surgical decompression, debridement, and drainage. 2. Broad-spectrum antibiotic and 3. Anti-inflammatory medication.
Other Information	Keep water and mild soap near work site.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media	Extinguish fire with the following: Use CO2, dry chemical or foam.
Hazards from Combustion Products	Combustion products may include: a complex mixture of airborne solid and liquid particulates and gases, including carbon monoxide, carbon dioxide, soot, oxides of sulfur, and unidentified organic and inorganic compounds.
Specific Methods	Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of decomposition.
Specific Hazards	Low hazard
Precautions in connection with Fire	If safe to do so, remove containers from path of fire. Keep containers cool with water spray. Avoid spreading liquid and fire by water flooding.

6. ACCIDENTAL RELEASE MEASURES

Spills & Disposal	Slippery when spilt. Avoid accidents, clean up immediately. CLEAN-UP METHODS - SMALL SPILLAGE (20L or less): Absorb or contain liquid with sand, earth or spill control material. Shovel up using non sparking tools and place in a labelled, sealable container for subsequent safe disposal. Put leaking containers in a labelled drum or overdrum. Scrub contaminated surfaces with detergent solution. Retain washings as contaminated waste. CLEAN-UP METHODS - LARGE SPILLAGE (more than 20L): Transfer to a labelled, sealable container for product recovery or safe disposal. Treat residues as for small spillage. Dispose according to local regulations. PERSONAL PRECAUTIONS: Extinguish naked flames. Remove ignition sources. No smoking. Avoid sparks. Evacuate the area of all non-essential personnel. Take precautionary measures against static discharge. Shut off leaks, if possible without personal risk. Avoid contact with skin, eyes, clothing. Do not breathe vapour. Ventilate contaminated area thoroughly.
------------------------------	---

7. HANDLING AND STORAGE

Precautions for Safe Handling	When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Prevent spillages. Ensure the appropriate personal protective equipment is used when handling this material.
Conditions for Safe Storage	Keep containers closed at all times. Store in cool place and out of direct sunlight. Store away from oxidizing agents. Check containers regularly for leaks.
Corrosiveness	Not corrosive

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards	Name	STEL		TWA		Footnote
		mg/m3	ppm	mg/m3	ppm	
	Mineral Oil			5		8 hour day
Other Exposure Information	Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current					

Material Safety Data Sheet

CS: 1.4.93

Page: 3 of 5

Infosafe No™ 5FUXG

Issue Date : August 2007

ISSUED by FUCHS

Product Name : **ISUZU CAB TILT (ISO68)**

Not classified as hazardous

	knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short term exposure limit (STEL). Occupational exposure limits: When an exposure standard has not been established by the National Occupational Health & Safety Commission for a material, a blanket recommendation of 5 mg/m ³ for respirable vapours, mists and dusts should be used.
Engineering Controls	Maintain concentration below recommended exposure limit. Special ventilation is not normally required due to the low volatility of the product at normal temperatures. However, in the operation of certain equipment or at elevated temperatures, mists or vapour may be generated and exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standard or where no exposure standard is allocated, as low as is reasonably practicable.
Respiratory Protection	Respirator not normally required. Airborne concentrations should be kept to lowest levels possible. If vapour, mist or dust is generated and the occupational exposure limit of the product is exceeded, use appropriate AS/NZS 1715/1716 approved half-face filter respirator suitable for organic vapours or air supplied respirator after determining the airborne concentration of the contaminant. Air supplied respirators should always be worn when airborne concentration of the contaminant or oxygen content of the air is unknown.
Eye Protection	Safety glasses, goggles or faceshield as appropriate.
Hand Protection	PVC, neoprene or nitrile rubber gloves.
Footwear	Enclosed footwear.
Body Protection	Overalls or similar protective apparel.
Hygiene Measures	Always wash hands before smoking, eating, drinking or using the toilet. If contamination occurs, change clothing. Avoid carrying contaminated rags in pockets or wearing soaked clothing. Discard internally contaminated gloves and footwear. Launder contaminated clothing before reuse.
Special Protective Measures	Will not burn unless preheated. Isolate from sources of heat, naked flame, or sparks.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Liquid
Appearance	Amber liquid
Odour	Mild
Melting Point	Less than 0 °C
Boiling Point	Greater than 300 °C
Solubility in Water	Not soluble
Solubility in Organic Solvents	Soluble in petroleum solvents
pH Value	Not relevant
Vapour Pressure	Less than 0.1 kPa
Vapour Density (Air=1)	Greater than 2 (Air = 1)
Colour	Clear yellow/amber
Density	0.86 - 0.93 kg/L @ 15 °C typical
Flash Point	Greater than 100 °C (PMCC)
Flammability	Combustible liquid C2 according to AS 1940.
Flammable Limits - Lower	Approximately 1.5%
Flammable Limits - Upper	Approximately 6.0%

Material Safety Data Sheet

CS: 1.4.93

Page: 4 of 5

Infosafe No™ 5FUXG Issue Date : August 2007 ISSUED by FUCHS

Product Name : ISUZU CAB TILT (ISO68)

Not classified as hazardous

Explosion Properties Not considered an explosion risk under normal conditions of use

Kinematic Viscosity Ranges from 9 - 748 mm²/s @ 40 °C

Other Information These physical data and other properties do not constitute a specification

10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions of use

Incompatible Materials Strong oxidising agents

Hazardous Reactions Will react with strong oxidising agents.

Hazardous Polymerization Will not occur

11. TOXICOLOGICAL INFORMATION

Toxicology Information Estimated Oral LD50 (rat): greater than 2000 mg/kg. This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, hydrocracking and hydrotreating. These oils have not been listed in the U.S. National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as carcinogenic or probably carcinogenic to humans.

Inhalation Inhalation of mists or aerosols can produce respiratory irritation.

Ingestion No adverse effects expected however large amounts may cause nausea and vomiting.

Skin Will have a defatting effect on the skin. Contact with skin may result in irritation.

Eye May cause watering of eyes.

Chronic Effects Prolonged or repeated exposure may result in irritation, with the possibility of dermatitis

Reproductive Toxicity Reproductive toxicity not expected.

Mutagenicity Mutagenic effects not known.

Carcinogenicity Product is not a known carcinogen.

12. ECOLOGICAL INFORMATION

Environ. Protection Do not allow material to enter drains or waterways.

13. DISPOSAL CONSIDERATIONS

14. TRANSPORT INFORMATION

Transport Information Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

15. REGULATORY INFORMATION

Poisons Schedule Not Scheduled

Packaging & Labelling No special packaging or labelling requirements.

16. OTHER INFORMATION

Literature References Useful references include the following: * NOHSC:2011 National Code of Practice for the Preparation of Material Safety Data Sheets
* NOHSC:1008 Approved Criteria for Classifying Hazardous Substances
* NOHSC:10005 List of Designated Hazardous Substances
* NOHSC:1005 Control of Workplace Hazardous Substances, National Model Regulations
* NOHSC:2007 Control of Workplace Hazardous Substances, National Code of Practice
* NOHSC:1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards

Material Safety Data Sheet

CS: 1.4.93

Page: 5 of 5

Infosafe No™ 5FUXG

Issue Date : August 2007

ISSUED by FUCHS

Product Name : **ISUZU CAB TILT (ISO68)**

Not classified as hazardous

- * NOHSC:3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note
- * NOHSC:1015 Storage and Handling of Workplace Dangerous Goods, National Standard
- * NOHSC:2017 Storage and Handling of Workplace Dangerous Goods, National Code of Practice
- * SUSDP, Standard for the Uniform Scheduling of Drugs and Poisons
- * ADG, Australian Dangerous Goods Code
- * MSDS of component materials

Last Change

Supersedes issue date:

Reason/s for revision:

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acchs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acchs Pty Ltd.
The compilation of MSDS's displayed is the intellectual property of Acchs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acchs Pty Ltd.