

Rev.

ENGINE SPECIFICATIONS

Engine Model	<u>Base Model 6BG1</u>
	<u>Model No. 6BG1TRD-01</u>
Customer	<u>Export Standard</u>
Application	<u>Generator</u>
Drawing No.	<u>E4-1024-118-1</u>
Emission Regulation	<u>EPA Tier-2, EC Stage- II</u>

Revision	Date	Revision Record	Issue No.
0	14-Jul-08	Issued	
:	:	:	:
:	:	:	:
:	:	:	:

ISUZU MOTORS LIMITED

Approval

Check

Issue

Sales Engineering Group

*S. NOGAMI**H. Harada**K. Sanada*

Powertrain Business Division

Satoshi Nogami

Hideaki Harada

Kaoru Sanada

Group Leader

Manager

Staff

Engine Specification

Rev.

Manufacturer	ISUZU MOTORS LIMITED		
Engine Model	Base Model	6BG1	Model No. 6BG1TRD-01
Application	Generator		
Engine type	Four cycle, water cooled, direct injection type, over head valve type		
No. of cylinders - bore x stroke	6 Inline - 105.0 mm x 125.0 mm		
Total piston displacement	6.494 litter		
Compression ratio	18		

Engine performance	Rating
Conditions	: Standard atmospheric condition
	: Breaking time 30 hours
	: With AC generator and cooling fan
	: Without air cleaner and exh. silencer
Rated output	Stand-by : 87.0 ±4.35 kW/ 1500 min ⁻¹ 100.3 ±5.02 kW/ 1800 min ⁻¹
	Prime : 73.6 kW/ 1500 min ⁻¹ 91.2 Kw/ 1800 min ⁻¹
Fuel consumption (at rated output power)	: Less than 239 g / kW.h
High idle speed	: Less than 1575 min ⁻¹ Less than 1890 min ⁻¹
Level set speed	: Less than 1630 min ⁻¹ 1923 ±4 min ⁻¹
Low Idle speed	: 1000 ±25 min ⁻¹
Type of fuel	: Diesel fuel (JPN:JIS-NO.2, US:ASTM-2D, EU:EN590)
Engine dry weight	: Approx. 450 kg
Engine Dimensions (L x W x H)	: 1172.6mm x 719mm x 952mm (with Fan)
Firing order	: 1 - 5 - 3 - 6 - 2 - 4
Rotating direction	: Clockwise viewed from cooling fan side
Valve device	: Overhead valve

Engine Specification

Rev.

Aspiration	:	Turbocharged
Fuel device	:	Injection pump, Bosch In-line type
Injection nozzle	:	Multi-hole type
Governor	:	Centrifugal variable speed type
Fuel feed pump	:	Plunger type, Integrated in injection pump
Fuel filter	:	Paper element type
Lubrication device	:	Gear type, Camshaft driven, Full forced pressure
Oil pressure indicate device	:	Oil pressure warning switch
Oil filter	:	Full flow, Paper element type
Cooling fan	:	580mm dia., blower, 7-blade, plastic
Water pump	:	Impeller type, Belt driven from crankshaft pulley
Thermostat	:	Wax pellet type
Starter	:	24V-4.5kW, Magnetically actuated type
Alternator	:	24V-25A, AC type, IC regulator build in type, Belt driven from crankshaft pulley
Pre-heating device	:	Glow plug, Convention type
Engine stop device	:	Fuel cut lever
Power take off	:	Without
Inclination limit	:	All direction 15deg
Lubrication oil capacity	:	Maximum 18.0 litter - Minimum 13.0 litter (Oil pan only)
Cooling water capacity	:	12 litter (Engine only)

Engine Specification

Rev.

Injection timing : 9 deg BTDC

Initial injection pressure : 18.9MPa

Compressive pressure : 3.04MPa at 200rpm engine speed

Valve clearance	Valve	Valve Clearance	Valve timing	
			Open	Close
	Inlet	0.4mm at cold	19.0deg BTDC	47.0deg ABDC
	Exhaust	0.4mm at cold	57.0deg BBDC	15.0deg ATDC

Paint : Gray

Recommended lubrication oil : API classification, Service CD class, SAE10W-30

Shipped loose parts

No.	Parts Name	Qty
1	Switch; Starter	1
2	Relay; Safety, Pulse	1
3	Relay; ENG. Stopper	1
4	Relay; Glow	1
5	Control Unit; QOS	1
6	Diode Asm	2
7	Gasket; Exh.	2
8	Stopper Asm; Engine	1

ISUZU

**6BG1TRD-01
Performance**

Condition	JIS D0006 / SAE J1349 / ISO15550
Atmospheric Condition	25 deg C
Braking time	30 hours
Cooling Fan	With 580mm dia., blower, 7-blade
Air Cleaner	NONE
Alternator	With (No Load)
Exhaust Silencer	NONE

